

特性:

- 用于时序控制的时间继电器
- 备有板前、板后的连接插座
- LED 再线指示灯，显示动作状态



ZQ3P(ST3P)

ZQ3P



电源电压: AC12V-380V DC12V-48V

延时范围

正启型号

性能参数

电源电压	DC12V-48V AC24V-380V50HZ/60Hz
功 耗	DC1.0W AC1.0VA
控制输出	5A220VAC
绝缘电阻	DC500V 100MΩ
介质耐压	BCC1500VAC BOC1000VAC
环境温度	-10℃~50℃
湿 度	35%~85%
寿 命	机械寿命:10 ⁷ 电气寿命:10 ⁵
重 量	≈ 50g

时间范围

型号	开关位置 延时类别	1		2		3		4	
		1	2	1	2	1	2	1	2
ZQ3P	A	0.05-0.5s	5s	2.3-30s	0.25-3m				
	B	0.1-1s	1-10s	5-60s	0.5-6m				
	C	0.5-5s	5-50s	50s	2.5-30m				
	D	1-10s	10-100s	10M	5-60m				
	E	5-60s	1-10m	60M	0.5-6h				
	F	0.25-2m	2.5-20m	2H	1-12h				
	G	0.5-4m	5-40m	4H	2-24h				

外形图、接线图、安装尺寸

